


36AWG Microcoaxial Specification

Diagram	Items	Items	RF-36-50Ω (unit:mm)
	Inner conductor	Material	Silver-plated copper wire
		AWG size	36AWG
		Composing	70.05±0.03
		OD (mm)	0.15±0.01
	Insulation	Material	PFA
		Nom. Thick.	0.055
		Nom.O.D.	0.26±0.02
		Color	White
	Shielding (1)	Material	Tinned copper alloy
		Type	Spiral
	Shielding (2)	Material	Cu metalized polyester tape
		Type	Wrapping
	Jacket	Material	PET Polyester tape
		Nom. Thick.	0.015
		Color	Red
		Nom.O.D.	0.36±0.02


UL:10005 80℃30V

Electrical Properties

Item	Unit	Spec.
Rating temperature	℃	80
Rating voltage	V	30
center conductor resistance @20 ℃	Ω/km	Max.1600
Insulation resistance @20℃	MΩ·Km	Min.1000
Allowable Current	A	0.7


Packing method

Packing Plate	Plastic packing
Standard Unit packing length	1000meter/reel



unit:mm

Item	D	d	W	a	h
P3R	130	80	90	10	20



Notice of application

Please store the cable in the dry and place,suggest the store conditions as follow: Temperature:20 ~ 30℃, Humidity: < 60%
When under the above storage condition suggested that uses in three months