

PS400-26.5G

High Frequency Phase Stable Cable (26.5 GHz)

Document No: SPEC-PS400-26.5G
Revision: A/0



Key Features & Capabilities:

- Operating Frequency: DC to 26.5 GHz with reliable VSWR performance.
- Solid PTFE dielectric providing high voltage endurance (1500V DC).
- Triple shielding (>90 dB effectiveness) for high isolation.
- Excellent phase stability vs. bending (± 0.3 °/GHz).
- Green FEP outer jacket rated for operating temperatures from -55°C to +125°C.

1. STRUCTURE & MECHANICAL CONSTRUCTION

Item	Layer Element	Material Specification	Nom. O.D. (mm)
1	Inner Conductor	Silver Plated Copper (SPC) (1/0.93 mm)	0.93
2	Insulation	Solid PTFE Dielectric	3.00
3	Inner Shield	Silver Plated Copper Strip	3.20
4	Interlayer	High Temperature Aluminum Foil	3.35
5	Outer Shield	Alloy Wire Braid	3.55
6	Jacket	Green FEP	4.00

2. ELECTRICAL & ENVIRONMENTAL RATINGS

Impedance	50 Ω	Max Operating Frequency	26.5 GHz
Velocity of Propagation	70%	Capacitance	94 pF/m
Screening Effectiveness	>90 dB	Withstanding Voltage	1500 V DC
Phase Change vs. Bending	± 0.3 °/GHz	Phase Change vs. Temp.	N/A
Min. Static Bend Radius	20.0 mm	Min. Dynamic Bend Radius	40.0 mm
Weight	0.041 kg/m	Operating Temperature	-55°C to +125°C

3. ATTENUATION & POWER HANDLING DATA

Calculation Formula: Insertion Loss IL = $K1 \cdot \sqrt{(F_MHz)}$ + $K2 \cdot F_MHz$ (K1 = 1.305096731, K2 = 0.003337)

Frequency (MHz)	Nom. Attenuation (dB/100m @ 25°C)	Max. Power Handling (W @ 40°C)
500	30.85	660
1000	44.61	456
2000	65.04	313
4000	95.89	212
6000	121.11	168
8000	143.43	142
10000	163.88	124
12400	186.71	109
16000	218.48	93
18000	235.16	87
26500	300.88	68